

Imprex

Extra light pine tar

General

Imprex is a mixture of Pine tar, tall oil pitch and tall oil. **Imprex** is a lighter and thinner tar with good penetration. It is practically free from acetic acid, phenols, contaminants and mineral products.

Range of application

The main area for usage is for wood, oakum and rope preservation. It is also intended for treatment of strand by natural fibres.

Instructions for use

Do not apply in thick layers when there is a risk of cracking and “bleeding” during hot weather. Paint with a brush.

NB! During rainy weather white spots may occur. They will disappear when the surrounding air is dry enough. Add linseed oil to avoid this.

Ensure good ventilation. Painting outdoors. Material Safety Data Sheet will be found at www.auson.se and painting instructions at www.tjarlek.se

Package

61100411 / 1-lit can
61100473 / 3-lit can
61100556 / 10-lit can
61110743 / 200-lit barrel

Technical data

Color:	Light brown
Density:	1, 00 ± 0,30 kg/lit
Coverage:	2-4 m ² / lit first coat (depending on the surface) 4-8m ² lit second coat (depending on the surface)
Drying time:	Does not dry completely but penetrates the surface whereupon the surface feels dry. This can take from several days to several weeks, depending on weather, planed or unplanned lumber, wood, thickness and how well the tar has seeped into the surface.
Thinning:	Gum turpentine or Alcohol. NB! Do not use White Spirit.
Cleaning:	Gum turpentine, Alcohol or soap and water
Storage:	24 Months (Unopened jar)

For further information we recommend the safety data sheet or instruction on package.

Issue: 2016-11-07 / AA